

# KASTOR WOOD-HEATED STOVES / KARHU-12 KARHU-20 KARHU-27 KARHU-37



MODEL	KARHU-12	KARHU-20	KARHU-27	KARHU-37
SAUNA (m <sup>3</sup> )	5–12	8–20	17–27	25–37
POWER (kW)	12	18	20	30
WIDTH X DEPTH X HEIGH (mm)	458 x 480 x 660	485 x 480 x 780	485 x 480 x 920	570 x 580 x 920
SAFETY DISTANCE FROM THE STOVE (mm)				
To the front	500 (1000*)	500 (1000*)	500 (1000*)	500 (1000*)
To the side	500	500	500	500
Back	500	500	500	500
Upwards	1200	1200	1200	1200
FLUE OPENING Ø TOP AND BACK (mm)	104	104	129	129
REAR FLUE OPENING HEIGHT FROM FLOOR (mm)	450	513	640	640
WEIGHT WITHOUT STONES (kg)	48	62	72	118
AMOUNT OF STONES (kg)	40	60	65	75

\*Recommendation

The stove has 2 adjustment legs in front. Safety distances in the table are to combustible materials, to non-combustible materials at least 50 mm.

### Choose the right size wood-heated stove from our wide selection.

Visible tile and glass surface increases the cubic capacity of the sauna. For each tile or glass wall square exceeding 2 m<sup>2</sup>, 3 m<sup>3</sup> is added to the sauna capacity. If the walls of sauna are of non-insulated timber, 25 % is added to capacity. In limiting cases always choose a bigger stove model.

### Choose the right size stove stones.

The diameter of the stones in a wood-heated stove must be at least 10 cm.

### OPTIONAL EXTRAS

Stones

Protective base

Connection tube H = 1000 mm

Angle tube 45°

Covering plate for angle tubes 45°

Covering plate for angle tubes 90°

NokiPois cleaning

www.kastor.fi